

rood

PGJ PERFORMANCE DATA

Nozzle	Pressure PSI	Radius ft.	Flow GPM	Precip in/hr ■ ▲	
0.50	30	14	0.42	0.41	0.48
	40	15	0.50	0.43	0.49
	50	16	0.58	0.44	0.50
0.75	30	15	0.64	0.55	0.63
	40	16	0.75	0.56	0.65
	50	17	0.85	0.57	0.65
1.0	30	18	0.85	0.51	0.58
	40	19	1.0	0.51	0.59
	50	19	1.1	0.57	0.66
1.5	30	21	1.3	0.57	0.66
	40	22	1.5	0.60	0.69
	50	22	1.7	0.67	0.77
2.0	30	24	1.7	0.55	0.64
	40	25	2.0	0.62	0.71
	50	25	2.3	0.71	0.82
2.5	30	27	2.2	0.58	0.67
	40	28	2.5	0.60	0.69
	50	28	2.8	0.68	0.79
3.0	30	30	2.5	0.53	0.62
	40	31	3.0	0.60	0.69
	50	31	3.4	0.68	0.79
4.0	30	33	3.7	0.65	0.76
	40	33	4.0	0.71	0.82
	50	34	4.3	0.72	0.83

Note:

All precipitation rates calculated for 180° operation.
For the precipitation rate for a 360° sprinkler, divide by 2.

